

3 5

Technical drawing of a rectangular metal enclosure, showing front, top, and side views. The drawing includes dimensions and callouts for specific features.

Dimensions:

- Overall width: 108
- Overall height: 108
- Top flange width: 20.4
- Bottom flange width: 20.4
- Flange thickness: 25
- Internal width: 60 ± 0.8
- Internal height: 83.5 ± 0.4
- Internal width (minimum): 73 (最小値)
- Internal height (minimum): 45
- Internal width (minimum): 26
- Internal height (minimum): 21.5
- Internal width (minimum): 25
- Internal height (minimum): 25

Callouts:

- 1: Bottom flange
- 2: Top flange
- 3: Right side flange
- 4: Left side flange
- 5: Internal width (minimum)
- 6: Internal height (minimum)
- 7: Internal width (minimum)

Other features:

- Two circular openings (Ø 27.1) on the front face.
- Two circular openings (Ø 27.1) on the top face.
- Two circular openings (Ø 27.1) on the bottom face.
- Two circular openings (Ø 27.1) on the left side face.
- Two circular openings (Ø 27.1) on the right side face.

7	アルミ箔	A L		—
6	六角ナット	SWCH	2	M4 三価クロメートめっき
5	塗代カバー本体	P V C	1	—
4	(+) 皿小ねじ	SWCH	2	M4×10 光沢クロメートめっき
3	(+) 皿タッピンねじ	SWCH	2	3×16 光沢クロメートめっき
2	六角ナット	SWCH	2	M4 三価クロメートめっき
1	本 体	P V C	1	—
符号	名 称	材 質	個数	備 考

		製品仕様図	
き	尺度	品名	スライドアウトレットボックス
	1/2		CDO-4AKGP12
き	第三角法	図番	OF55071B3 

未来工業株式会社